Doc	ument Viewer				
Turnitin Originality Report					
Processed on: 19-Oct-2021 07:10 WIB ID: 1677568070 Word Count: 2468 Submitted: 1 Effect Of Plasma Carburising Process On Alumi By Sujita Darmo	Similarity Index	Similarity by S Internet Source Publications: Student Papers:	Source s:	9% 14% 5%	
include quoted include bibliography excluding matches < 1%	mode: quickview	(classic) report	✓ Cł	nange mode	•
3% match (Internet from 18-Sep-2021) <u>https://www.hsd-fmsb.org/index.php/hsd/article/view/2721</u> 2% match (publications) <u>F B Darsono, S T Koin. "The Effect of T6 Heat Treatment on 70</u> <u>Conference Series: Materials Science and Engineering, 2021</u>	75 Aluminum on its H	ardness and Ten	nsile Stre	ngth", IOP	×
2% match (publications) <u>S. Ahmad, Mehboob Sadiq, S. Hussain, M. Shafiq, M. Zakaullah</u> <u>from plasma focus", Review of Scientific Instruments, 2006</u>	<u>ı, A. Waheed. "Cataly</u> ı	<u>tic action of β so</u>	ource on a	<u>x-ray emis</u>	sion _×
1% match (publications) Hassan, M "Surface modification of AlFe"1"."8Zn"0"."8 alloy by using dense plasma focus", Vacuum, 20061024					×
1% match (publications) <u>Mohammad Taghi Hosseinnejad, Zohreh Ghorannevis, Mahmoo</u> "Investigation of Effective Parameters on Metal Nitride Depositi Axial and Angular Positions", Journal of Fusion Energy, 2015	<u>d Ghoranneviss, G. R</u> on by Plasma Focus D	<u>eza Etaati, Marz</u> Device: Number	ieh Shira of Shots	<u>zi.</u> and Subst	rate_×
1% match (publications) <u>Mehboob Sadiq, Sarfraz Ahmad, Muhammad Shafiq, Muhamma</u> Irradiation in a Dense Plasma Focus", Plasma Processes and Po	ad Zakaullah. "Enhanc Ilymers, 2007	ed Crystallinity	of PTFE Ł	<u>oy Ion</u>	×
1% match (Internet from 08-Apr-2016) https://www.ukessays.com/essays/biology/deposition-of-titani	um-nitride-thin-films-	<u>biology-essay.pl</u>	<u>hp</u>		×

1% match (Internet from 26-Feb-2020) <u>https://link.springer.com/article/10.1007%2Fs10894-013-9596-y</u>	×
1% match (Internet from 16-Sep-2021) http://researchinventy.com	×
1% match (Internet from 24-Oct-2020) <u>http://docplayer.net</u>	×
1% match (publications) <u>Manova, D "Oxygen behaviour during PIII-nitriding of aluminium", Nuclear Inst. and Methods in Physics Researcl 200105</u>	<u>h, B,</u>
1% match (publications) <u>Hussain, T "Deposition of titanium nitride on Si(100) wafers using plasma focus", Nuclear Inst. and Methods in Pl Research, B, 200903</u>	<u>hysics</u>
1% match (Internet from 07-Sep-2017) <u>http://prr.hec.gov.pk</u>	×
1% match (student papers from 30-Oct-2014) <u>Submitted to Visvesvaraya Technological University on 2014-10-30</u>	×
1% match (Internet from 14-Oct-2021) http://eprints.unram.ac.id	×
1% match (publications) <u>M Hassan. "Nitriding of titanium by using an ion beam delivered by a plasma focus", Journal of Physics D Applied</u> <u>02/07/2007</u>	Physics, 🗙
1% match (Internet from 21-Apr-2016) http://nectar.northampton.ac.uk	×
1% match (Internet from 28-May-2020) <u>https://www.oalib.com/paper/60757</u>	×

GSJ: Volume 8, Issue 5, May 2020, Online: ISSN 2320-9186 www.globalscientificjournal.com <u>EFFECT OF PLASMA</u> <u>CARBURISING PROCESS ON ALUMINUM ALLOYS (AL-Cu 2118 SERIES</u>) Sujita Darmo1, Rudy Sutanto2 1,2Faculty of Engineering, Departmen of Mechanical Engineering, Mataram University, Matara, Indonesia, 062-370-636126 E-mail:

sujita@unramac.id KeyWords Plasma carburizing, aluminum allovs, focus shot, methane, surface hardness number, ABSTRACT In the present research a detailed effect of carbon-ions implantation in aluminum alloys (Al-Cu 2118 series) specimens at the room temper- ature by using a mathertype plasma focus device, operated with methane (a new process of plasma carburizing). Same treatment condition which has been reported in this study, fired at 15 kV giving a peak discharge current of about 150 kA over multiple focus shots. The results obtained indicates that the variation in focus shots has a significant impact on the surface hardness number of the Al-Cu 2118 series. The surface hardness number of the specimen increases continuously by increasing the ion content to 15 focus shots during the plasma carbu-rizing process and reaches a maximum surface hardness number of 160 Kg.m-2, which is almost six times compared to the surface hardness number of Al-Cu 2118 series which is untreated. Enhanced surface hardness can be associated with the formation of Al4C3 and amorphous carbon phases. Based on this investigation, a plasma carburizing device was found to be an efficient device to obtain a harder aluminum alloy surface in a room temperature. INTRODUCTION Aluminum and its alloy like that Al-Cu 2118 series are popular for their extensive use in automotive piston, rail, marine and aero-space industries. It is widely used in electrical shielding, electronic circuits and devices making, food and pharmaceutical packaging, water treatment and house decoration owing to its nonmagnetic, very low sparking, less trashing, nontoxic and noncombustible be- havior Febry et al., (2018) and Subbiah et al., (2018). It's outstanding properties of light weight, good malleability and formability, high corrosion resistance, excellent electrical and thermal conductivity, better light reflectivity and good recyclability are making the Al-Cu 2118 series an essential and ideal metal for today's advanced technological world. However, its insufficient wear resistance with low surface hardness number thermal and chemical stability limits its use for commercial and industrial purposes Li et al., (2019) and Pirizadh jrandoost et al., (2012). The high surface hardness number and high strength to weight ratio of Al-Cu 2118 series for its application in the area of sliding machine parts for height saving purpose but its tensile strength and the low surface hardness (lower than that of mild steel and iron alloyed materials mainly used for these parts at present) offer a major barrier. There- fore surface modification of AI-Cu 2118 series, to improve wear and corrosion resistance, surface hardness and lower coefficient of friction, is intensively required to enhance its utilization in all fields of interest. Presently, nitriding, oxidizing and carburizing of alu- minum by employing different techniques are commonly used to obtain tribologically and mechanically improved aluminium surface. Nitriding of aluminum is the most studied and investigated process for surface modification to achieve desired combination of physi- cal and chemical properties. like high hardness, excellent wear resistance, high electrical and corrosion resistance, very good optical properties, and high thermal and chemical stability. For example Ghulam et al., (2009), Patama et al., (2003) and Balanovski et al., (2017) reported that formation of hard aluminum nitride (AIN) layer on the surface can prolong the life time of aluminum. In spite of all the properties the AI-Cu 2118 series the surface of AIN layer is often morphologically rough containing deep grooves and cracks and is considered unsatisfactory for industrial application. Also the physical parameters' effects on tribological and mechanical prop- erties of AIN are not yet well understood. Carburizing of aluminum however could provide a suitable alternative of nitriding for im- proved mechanical and tribological properties in a similar way as in the case of iron and steel Leyland et al., (2003) and Afza et al., (2019) . This inspired to study the ability of plasma focus for carburizing of Al-Cu 2118 series. MATERIALS AND METHODS FOR EXPERIMENT Aluminum alloys (AI-Cu 2118 series) specimens before treatment was tested by spectrometer with objective to understand consist- ence of material specification of Al-Cu 2118 series where standard ASTM can be seen in Table 1. Table 1. Chemical Composition of Al-Cu 2118 series without treatment Element % Si 0.01 Fe 0.1089 Cu 1.133 Mn 0.0162 Mg 1.8635 Zn 5.8113 Ti 0.0916 Cr 0.0916 Pb 0.0015 Sn 0.004 Al 90.75 The Plasma focus system consists of a coaxial electrode assembly with an anode of aluminium rod having an effective length of 100 mm and a diameter of 15 mm

located at the centre surrounded by six equidistant symmetrical copper rods forming cathode with cathode to anode radius ratio of 3.5, shown in Figure 1. The anode is slightly tapered towards the open end to enhance the emission of charge particles. A Pyrex glass insulator sleeve of 23 mm breakdown length, with an external diameter of 24.5 mm and wall thickness of 2 mm, is used to separate the anode from the cathode base plate. A field distortion type spark gap is used to transfer energy from the capacitor bank to the electrodes of plasma focus system. The system is operated in a gas flow mode to get rid of the impurities. Figure 1. Plasma Carburizing Layout RESULT AND DISCUSSION Good carburizing plasma is obtained at a pressure of 0.5 mbar methane gas at a filling voltage of 15 kV. Optimal charging voltage and charging pressure values are kept constant during the experiment. $10 \times 10 \times 0.3$ mm aluminum specimens are mechanically polished to the mirror surface before being positioned at an axial distance of 8 cm from the anode end. Al-Cu 2118 series aluminum alloys are placed between the ion sources which are used to avoid the effects of the ion beam emitted during conditioning shots. Rapid re- sponse photo conductive GaA detectors closed with 50 µm diameter pin holes are used at a distance of 8 cm in front of the anode end to measure the ionic energy emitted from plasma carburizing. The spatial distribution of the ion beam reaching the specimen is obtained by placing a CR-35 trace detector at a distance of 5 cm in front of the tip of the central anode. The performance of a plasma carburizing device with a sharp focus and energetic ion emissions is the most important in this type of experiment. Signals from GaA detectors, voltage probes, and Rogowski coils are continuously monitored with a Gould 3072 A oscilloscope with four-channel digital storage. Figure 2. Al-Cu 2118 Series Surface Specimens After Plasma Carburizing Treatment Furthermore, ion energy is generated around 25-250 keV. The trace on the surface of the specimen shown in figure 2. is the result of etching the detector for four hours in a dilute solution of 6N-NaOH at 75 oC. Based on Figure 2. it appears that the ion distribution is largely uniform. It can be observed that several ionic populations with different energy values also exist. Track density found varies from about 6×104 tracks mm-2 for directions 0 ° to 5 \times 104 tracks mm-2 for directions ± 30 °. Surface Hardness Number Results The surface hardness as a function of the indentation depth is measured with Vickers micro hardness tester, as shown in the Figure 3. The loads 500 gr are applied to obtain micro hardness. Figure 3. Surface Hardness Number Speciment with Plasma Carburizing The surface hardness number of the specimen increases continuously by increasing the ion content to 15 focus shots during the plasma carburizing process and reaches a maximum surface hardness number of 160 Kg.m-2, which is almost 6 times compared to the surface hardness number of Al-Cu 2118 series which is untreated. Enhanced surface hardness can be associated with the formation of Al4C3 and amorphous carbon phases. A slight decrease in surface hardness number occurs. When the sample is treated with more than 15 focus shots, a decrease in surface hardness number is observed. This may be caused by poor formation of the crystalline phase and damage to the carbide phase due to increased ion irradiation. The Results of SEM Test Figure 4. are the surface morphology of pristine and plasma carburized samples is studied by obtaining micrographs using a JEOL JSM-5910 scanning electron microscope (SEM). Based on observations, no significant features except the fine scratches induced by polishing are observed for a pristine sample. The surface smoothness seems to increase with increasing number of focus shots upto 15. It is assumed that upto 15 focus shots, in addition to AI4C3 phase and C-C clusters formation, the energy density of ions is suitable to remove certain voids, asperities and rough particles by sputtering and etching processes and a smooth carburized surface is achieved. When the number of focus shots reaches to 20, surface layer becomes slightly rough with wavy wrinkle-like structure, which represents a thin superficially molten layer of the substrate. High doses of carbon and unbound carbon result in surface swelling of substrate increasing its roughness as in the case of nitriding. Surface treated with 25 focus shots shows rough surface and some microcracks with low density small pores. It is assumed that high fluences of ion, generated by stable and strong focusing action, deliver excessive energy to substrate, causing sputtering and etching and hence resulted in surface damage

and roughness along with a very few small pores. The guenching after the transient temperature rise with short pulse ion beam resulting in the brittleness of the sample may be the reason behind the development of micro cracks a b c d e f Figure 4. The Result of SEM Test Specimen with Plasma Carburizing, a. Untreated b. 5 Shots c. 10 Shot c. 15 Shot d.20 Shot The variation of carbon and oxygen concentration with increasing number of focus shots is obtained by EDX attached with the SEM. The oxygen peak in the untreated sample is present because of native oxide layer. The concentration of oxygen is reduced by ion sputtering process with increasing number of focus shots but a negligible amount remains present. This may be due to re-oxidation of near surface region by residual gas and by the process of ion beam mixing. The concentration of carbon increases with increasing number of focus shots as expected. CONCLUSIONS The Plasma Carburizing process with methane using a plasma focus device Mathertype in a double focus shot can increase the sur- face hardness number of Al-Cu 2118 series. These results suggest the parameters for a plasma carburizing device to obtain a quality carburizing aluminum alloys surface. About six times the increase in surface hardness is caused by the hexagonal Al4C3 phase. Based on this investigation, a plasma carburizing device was found to be an efficient device to obtain a harder aluminum alloy sur- face in a room temperature environment and shorter time. Acknowledgment The authors thank Prof. Rudy Soenoko, Prof. Anindito are acknowledged for invaluable endless collaboration. Prof. I.G.NWardhana Director Postgraduated Doctor Mechanical Engineering Program Brawijaya University permission to use of laboratory and other resource materials. References [1] Afzal, Naveed & Rafigue, Mohsin & Javaid, Wajeeha & Ahmad, Riaz & Faroog, Ameeg & Saleem, Murtaza & Khalig, Zubair, Influence of Carbon Ion Implantation Energy on Aluminum Carbide Precipitation and Electrochemical Corrosion Resistance of Aluminum, Nuclear Instruments and Methods in Physics Research Section B Beam Interactions With Materials and Atoms, 2019, 436.pp. 84-91. [2] Li, G. Meng, Liang, Y. Long, Yin, C. Hong, Sun, H., & Zhu, Z. Long, Study Of M50NIL Steel Under Carburizing and Nitriding Duplex Treatment. Surface and Coatings Technology, 2019, 375, pp.132–142. Https://Doi.Org/10.1016/J.Surfcoat.2019.07.017. [3] Febri Budi Darsono, Teguh Triyono, And Eko Surojo, The Effect of Case Hardening Treatment on Aluminum 7075 Toward Its Hardness and Tensile Strength, AIP Conference Proceedings 1931, 030058, 2018, Https://Doi.Org/10.1063/1.5024117 [4] Yang, Y., Yan, M. F., Zhang, S. D., Guo, J. H., Jiang, S. S., & Li, D. Y. Diffusion Behavior Of Carbon And Its Hardening Effect On Plasma Carburized M50nil Steel: Influences Of Treatment Temperature And Duration, Surface And Coatings Technology, 2018, 333, pp.96–103. Https://Doi.Org/10.1016/J.Surfcoat.2017.10.068. [5] Subbiah, R., & Pradeep, Y., The Wear Characteristics of AISI310 Grade Stainless Steel Material By Carburizing and Carbonitriding Process, International Journal of Mechanical And Production Engineering Research And Development, 2018, 8(6), 159–164. Https://Doi.Org/10.24247/Ijmperd dec 201818. [6] Sugawara, Yu & Inoue, Waka & Muto, Izumi & Hara, Nobuyoshi, A Methodology For Fabrication Of Highly Pitting Corrosion- Resistant Type 304 Stainless Steel By Plasma Carburizing And Post-Pickling Treatment, Journal Of The Electrochemical Society, 2018, 165. C441-C449. 10.1149/2.0081809jes. [7] Balanovskii, A & Grechneva, M & Huy, Vu & Zhuravlev, D., New Plasma Carburizing Method. Iop Conference Series: Earth And Environmental Science, 2017, 87. 092003. 10.1088/1755-1315/87/9/09 2003. [8] Pirizadheirandoost, Somayeh & Bakhshzad Mahmoudi, Mehdi & Ahmadi, Elnaz & Moradshahi, Masoud, The Corrosion Behavior Of Carburized Aluminum Using Dc Plasma. Journal Of Metallurgy, 2012, 2012. 10.1155/2012/258021. [9] Kula, P., Pietrasik, R., & Dybowski, K., Vacuum Carburizing Process Optimization, Journal Of Materials Processing Technolo- gy, 2005, 164– 165, 876–881. Https://Doi.Org/10.1016/J.Jmatprotec.2005.02.145. [10] Ghulam Murtaza, S.S. Hussain, Mehboob Sadig, M. Zakaullah, 2009, Plasma Focus Assisted Carburizing Of Aluminium, Thin Solid Films, 2009, Volume 517, Issue 24, pp.6777-6783, Issn 0040-6090, Https://Doi.Org/10.1016/J.Tsf.2009.05.065. (Http://Www.Sciencedirect.Com/Science/Article/Pii/S0040609009010153). [11] Patama Visuttipitukul, , Tatsuhiko

Aizawa And Hideyuki Kuwahara, Advanced Plasma Nitriding For Aluminum And Aluminum Alloys, Materials Transactions, 2003, Vol. 44, No. 12 (2003) Pp. 2695 To 2700 [12] Leyland, A., Lewis, D. B., Stevensom, P. R., & Matthews, A. (1993). Low Temperature Plasma Diffusion Treatment Of Stainless Steels For Improved Wear Resistance. Surface And Coatings Technology, 62(1–3), 608–617. Https://Doi.Org/10.1016/0257- 8972(93)90307-A. [13] Samandi, M., Shedden, B. A., Smith, D. I., Collins, G. A., Hutchings, R., & Tendys, J., Microstructure, Corrosion And Tribological Behaviour of Plasma Immersion Ion Implanted Austenitic Stainless Steel. Surface And Coatings Technology, 1993. 59(1–3), 261– 266. Https://Doi.Org/10.1016/0257-8972(93)90094-5. <u>GSJ: Volume 8, Issue 5,</u> May 2020 ISSN 2320-9186 854 <u>GSJ: Volume 8, Issue 5, May 2020 ISSN 2320-9186</u> 855 <u>GSJ: Volume 8, Issue 5,</u> May 2020 ISSN 2320-9186 856 GSJ: Volume 8, Issue 5, May 2020 ISSN 2320-9186 857 <u>GSJ: Volume 8, Issue 5,</u> May 2020 ISSN 2320-9186 858 <u>GSJ: Volume 8, Issue 5, May 2020 ISSN 2320-9186</u> 859 GSJ© 2020 www.globalscientificjournal.com GSJ© 2020 www.globalscientificjournal.com