

Document Viewer

Turnitin Originality Report

Processed on: 19-Oct-2021 10:07 WIB

ID: 1677713119

Word Count: 3219

Submitted: 1

Influence of Coconut Shell Charcoal Powder
Fi... By Sujita Darmo

Similarity Index

18%

Similarity by Source

Internet Sources:	9%
Publications:	12%
Student Papers:	7%

[include quoted](#) [include bibliography](#) [excluding matches < 1%](#)
[print](#) [refresh](#) [download](#)

mode: quickview (classic) report

Change mode

3% match (Internet from 05-Oct-2021)

<http://www.eprints.unram.ac.id>

3% match (publications)

[Umar Nirmal, B.F. Yousif, Dirk Rilling, P.V. Brevern. "Effect of betelnut fibres treatment and contact conditions on adhesive wear and frictional performance of polyester composites", Wear, 2010](#)

2% match (Internet from 21-Nov-2020)

<https://www.irjet.net/archives/V7/i4/IRJET-V7I41198.pdf>

2% match (publications)

[K. Mysamy, I. Rajendran. "Influence of Fibre Length on the Wear Behaviour of Chopped Agave americana Fibre Reinforced Epoxy Composites", Tribology Letters, 2011](#)

1% match (publications)

[A. Shalwan, B.F. Yousif. "In State of Art: Mechanical and tribological behaviour of polymeric composites based on natural fibres", Materials & Design, 2013](#)

1% match (Internet from 27-Sep-2021)

<http://www.ijres.org>

1% match (publications)

[Yousif, Belal F. "Adhesive Wear Characteristics of Natural Fiber-Reinforced Composites", Wear of Advanced Materials Davim/Wear of Advanced Materials, 2013.](#)

1% match (student papers from 07-Jun-2018)

[Submitted to University of Southern Queensland on 2018-06-07](#) 

1% match (publications)

[N.S.M. El-Tayeb. "Abrasive wear performance of untreated SCF reinforced polymer composite", Journal of Materials Processing Technology, 2008](#) 


1% match (publications)

["Tribological Applications of Composite Materials", Springer Science and Business Media LLC, 2021](#) 

1% match (Internet from 21-Apr-2021)

<https://dokumen.pub/green-composites-for-automotive-applications-9780081021774-0081021771.html> 


1% match (publications)

[Gangadhara Rao Ponugoti, Gopala Krishna Alluru, Pandu R. Vundavilli. "Response Surface Methodology Based Modelling of Friction-Wear Behaviour of Al6061/9%Gr/WC MMCs and Its Optimization Using Fuzzy GRA", Transactions of the Indian Institute of Metals, 2018](#) 

1% match (publications)

[Umar Nirmal, Jamil Hashim, Sajjod TW Lau, Yuhazri My, BF Yousif. "Betelnut fibres as an alternative to glass fibres to reinforce thermoset composites: A comparative study", Textile Research Journal, 2012](#) 

1% match (publications)

[Bajpai, P. K., I. Singh, and J. Madaan. "Frictional and adhesive wear performance of natural fibre reinforced polypropylene composites", Proceedings of the Institution of Mechanical Engineers Part J Journal of Engineering Tribology, 2012.](#) 

1% match (publications)

[T. P. Mohan, K. Kanny. "Tribological Studies of Nanoclay Filled Epoxy Hybrid Laminates", Tribology Transactions, 2016](#) 

1% match (student papers from 18-Jan-2021)

[Submitted to Universitas Mataram on 2021-01-18](#) 

[Influence of Coconut Shell Charcoal Powder Filler on the Tribological Properties of Natural Fiber Reinforced Polymer Composite](#) Sujita Darmo¹, Rudy Sutanto² ^{1,2}Lecturer, Department of Mechanical Engineering Faculty Engineering University of Mataram Majapahit Street 62 Mataram 83125 Indonesia. -----

----- Submitted: 01-05-2021 Revised: 09-05-2021 Accepted: 10-05-2021 -----

----- ABSTRACT:In the current work to investigate, coconut shell charcoal powder (CSCP) as a composite filler and Musa acuminata stem fiber (MASF) which is used as a reinforcement to study and analyze the potential improvement in wear-resistant property of epoxy matrix composites. For the first time, this finds applications, especially in brake pads where friction exists. Thus, it can be prepared with non- toxic and locally

available cheap fibers to produce a prospective tribo material. MASF reinforced with epoxy composites was prepared with variations of CSCP 10%, 20%, 30%, and without CSCP. The composite was prepared by hand layup and open mold technique with [a fiber length of 20 mm and](#) fiber percentage [of 30 wt.%](#) for all kinds of samples. A computerized pin on disc machine was used to test tribological properties of the composites and the test was conducted with various parameters namely type of treatment, applied [normal loads \(15, 20, 25, and 30 N\), and sliding speed \(1.5, 2.0, and 2.5 m/s\) for](#) a constant [sliding time of 15 min](#) under dry condition. From the result, it was concluded that the weight loss of addition of CSCP filler to natural fiber reinforced epoxy composites got reduced by 15% and 39%, while the coefficient of friction was also decreased by 41% and 39% respectively. [A scanning electron microscope \(SEM\) was used to observe the worn surface](#) and wreckage in [the](#) tested composite samples. As a conclusion, experiment results and microscope observation indicate that 30 wt.% of addition of CSCP filler to natural fiber reinforced epoxy composites exhibited good wear resistance compared to other. KEYWORDS: Epoxy matrix composites, Coconut shell charcoal powder, Musa acuminata stem fiber, Wear resistance I. INTRODUCTION The day, composites have become attractive materials for numerous applications because of their many unique technical properties which include lightweight, high productivity and cost-effectiveness. In the context of economic and ecological way of making fiber-reinforced polymeric composites, the natural fibers are found to be most attractive during the past few centuries. Traditionally fabricated steel materials with specific higher strength, surface hardness, density were replaced by composite materials. As an alternate to metals, the composite materials are used in tribological parts such as pad brake plastics gears, artificial [joints, guide rails, sliding bearings, and so on](#) [1]. This is due to the preferred characteristics of the polymer matrix composite such as self-lubrication and noise reduction. Tribological performance of synthetic fibres such as glass, carbon and Kevlar reinforced polymeric composites has been extensively studied [2-4]. Nowadays, natural fibers are becoming an alternative reinforcement for polymers due to their excellent advantages, i.e. renewable, environmental friendly, low cost, the flexibility of usage, lightweight, naturally recyclable, and biodegradable. Many applications [such as housing construction materials, furniture, and automotive parts](#). From a mechanical point of view, it has been proven that natural fibers enhanced the mechanical properties of neat polymer matrix composites [5-6]. Natural fibers are generally sustainable and used in automobile industries. Automobile industries seized the initiative to incorporate the use of plant-based fibers and composites in manufacturing car components that prove the feasibility and increase in production of automotive parts. For example, natural fibers such as sisal, hemp, and flax fibers were commonly used as the interior indoor padding, floor panels, lining for seat backs whereas cotton fibers are used in soundproofing material and coconut fibers to manufacture head restraints and back cushion [7-8]. In polymer matrix composites, several limitations were found in substituting natural fiber with conventional fiber. Among several disadvantages, the hydrophilic nature of the reinforcement fiber which relies upon the presence of non-crystalline parts and voids content is the most common important issue. To obtain good tribological and mechanical properties as well as to minimize the moisture absorption capacity of natural fibers, number of techniques like surface treatment, additives, and coating have been used nowadays [9]. [Nevertheless, less work is found on the effects of natural fibers on the tribological performance of polymeric matrix composites.](#) In general, [the](#) tribological performance of polymeric matrix composites is influenced by many factors such as test technique and operating parameters [5]. The effects of untreated sugarcane fibres [on the abrasive wear characteristics of polyester composites was studied](#) [10-11]. He found that the worn surfaces of the composites were highly damaged and different types [of wear mechanisms took place during the abrasion tests](#), i.e. [plastic deformation, micro cutting in the matrix](#), pitting, ploughing, [and](#) fragmentation of wear. From the above, it is observed that there are very few studies on the effects of filler and natural fiber on the adhesive wear performance of polymeric matrix composites. Consequently, prediction of the adhesive

wear characteristics of such composites is a difficult task. Thus, there is a necessity for a better understanding of the effects of the filler and natural fibers reinforcement matrix composites on the tribological properties. This study aims to determine the tribological properties of Musa acuminata stem fiber reinforced epoxy composites with coconut shell charcoal powder as a composite filler, for the feasibility of these composites as an alternative solution to the replacement material for brake pad categorized as Multi-Purpose Vehicle (MPV) which in its application is closely related to safety usage, especially in the automotive sector. II. EXPERIMENTATION The coconut shell used in this study is charcoal. The coconut shell charcoal is then blended, sieving with a size range of 200 and 500 mesh. Soaking the coconut shell charcoal powder with a solution of stearic acid in acetone (1% by weight) for 2 hours. Next, drying the coconut shell charcoal powder using an oven for one day. Musa acuminata plant available North Lombok district, West Nusa Tenggara state, Indonesia which comes under the family of Musaceae. The MASF extraction process includes Musa acuminata plant stem dipped in water for 1 week in order to separate fibers from stem through microbial degradation and further by using freshwater, the soaked stem is cleaned and dried in sun light for a week. Combing process was performed with metal teeth brush for extracting the fiber from the stem. Coconut shell charcoal powder. Musa acuminata stem fibers It took almost 5-7 days for this entire process of extracting fiber from the stem. Extracted fiber is soaked in 5 wt.% NaOH solution for an hour at room temperature and then washed in running water to remove excess NaOH. Finally, distilled water is used to wash the fiber and the fibers are dried in the direct sunlight for a period of week time. Epoxy composite reinforced with MASF was prepared with four different conditions of filler composite such as CSCP 10%, 20%, 30%, and without CSCP. MASF length 30 mm and MASF percentage of 30 wt.% for all kinds of samples. In laboratory, the chopped fiber and resin were mixed. Manual stirring took place to scatter the fibers in the matrix for a sufficient time, whereas hand layup and open mould technique were used to prepare the samples. Mould of glass test tube with dimension of 75 mm length and 10 mm diameter was used. The sample was taken out of the mould after it was cured for 24 h and the entire process was held at a room temperature of around 29 °C. The samples were labeled as NCSCP, CSCP 10, CSCP 20, and CSCP 30 according to variations in content filler composite. Wear resistance testing using Pin-on-disc (POD) tribometer controlled by computer was used to perform wear test ASTM standard of G99-95 with the dimension of 10 mm diameter and length 15 mm. Wear specimen was placed against the stainless steel with a loads of 15, 20, 25 and 30 N at different sliding velocities of 1.5, 2.0 and 2.5 m/s corresponding with 100, 200 and 250 rpm used for the test duration of 10 min at a radial sliding distance of 80 mm. Immediate contact was made between the counter surface of the specimen and the disc by creating roughness on the specimen surface with the use of water proof silicon. The disc and samples were cleaned by the use of acetone before conducting the test. Before the experiments, the sample weight is measured as W1 and weight of the specimen after the wear test is noted as W2 with the help of electronic weighing machine of 0.001 gm as least count. The weight difference between the weight of the specimen before the wear test and after the wear test is called as weight loss (ΔW). The following equations are used to calculate the weight loss (ΔW), coefficient of friction (μ) and wear rate respectively. By using Eq. (1), Eq. (2) and Eq. (3) with different speed and different load, the weight loss, coefficient of friction and wear rate of the specimen were determined [24]. Weight loss (ΔW) = W1 - W2 (1) Coefficient of friction (μ) = f / N (2) Wear rate (WR) = ΔW / (3) ρL where, μ is coefficient of friction, f = frictional force, N = normal load, ρ = density and L = sliding distance. The test was conducted at room temperature of 29 °C and relative humidity of 65%. Morphological analysis used scanning electron microscope (Model VEGA 3 TE SCAN) for studying the surface of the wear tested specimen. Thin layer of sputtered gold was coated on the worn surface of all the tested composite specimens to improve electrical conductivity and to obtain better images. III. OBSERVATIONS FROM THE TEST WEAR RESISTANCE Epoxy composite material reinforced with MASF and CSCP filler has been examined based on different conditions of filler composite such

CSCP 10%, 20%, 30%, and without CSCP with different velocity and varying loads. Wear resistance of polymer material depends on the applied load, mechanical characteristics and chemical bonding of material [24]. When compared to conventional material surface, surface of polymeric material is smooth. For wear analysis, 15 N-30 N load is applied at an interval of 5 N for the velocity of 1.5, 2.0, and 2.5 m/s. Less than 15 N load and 1.5 m/s velocity was predicted as negligible. MASF at velocity of 2.5 m/s. Wear rate of epoxy composite reinforced with Wear resistance measurement apparatus Wear Rate (mm³/min) NCSCP CSCP 10 15 10 5 0 CSCP20 10 15 20 Load (N) 25 30 CSCP30 35 Wear rate of epoxy composite reinforced with MASF at velocity of 1.5 m/s. NCSCP CSCP10 CSCP20 CSCP30 Wear Rate (mm³/min) 14 12 10 8 6 4 2 0 10 15 20 25 30 35 Load (N) Wear rate of epoxy composite reinforced with MASF at velocity of 2.0 m/s. The wear rate of MASF reinforced epoxy composite, without CSCP filler, CSCP 10%, 20% and 30% is different at 100 rpm, 200 rpm and 250 rpm with a load variation of 15 N, 20 N, 25 N and 30 N with constant sliding for 10 minutes. When compared with epoxy composite with filler, CSCP 10%, 20% and 30% reinforced with MASF, composites with different loads and different speeds, that's all found epoxy composites without CSCP fillers has a high wear rate. Under different loads and speed. It was found that the addition of the CSCP filler experienced less wear rate when compared to composites without filler CSCP. Less wear means better wear resistance. Additional 30% CSCP filler has the best wear resistance quality. The reason is a good interface bond. Composite without CSCP filler occurs cracking, plastic deformation, wear, poor adhesion, pulling of fibers and dirt, wear rates increase in composite. The higher wear rates for the epoxy composites cause the fibers to be pulled easily from the matrix, but still less tensile and peel of fibers in silane treated composites. This may be due to the influence that CSCP filler fed fibers are preferred due to polymer cross-linking. The presence of good MASF CSCP filler fibers in epoxy composites decreased wear rate and friction appearance and similar results reported by [4]. When comparing wear rates for all shear speeds, loads applied and maintenance fibers, composites without CSCP fillers showed a greater reduction in wear rates compared to other samples. The addition of the CSCP filler leads to formation of better interlocking bonds between matrices and fibers and hence composites show lower wear rate or increased wear resistance [12]. SEM micrographs of epoxy composite-MASF-NCSCP at 30 N applied load and 2.5 m/s sliding velocity. The micrograph of epoxy composite- MASF-NCSCP at 30 N applied load and 2.5 m/s sliding velocity, under this condition, it can be seen that the MASF are slightly debonded (marked as „,De“). Furthermore, the wear mechanism in the resinous region is predominated by deformation. Because there is no addition of filler, the matrix and fiber bonds are not homogeneous. The micrograph of epoxy composite MASF-SCSP10% at 30 N applied load and 2.5 m/s in can be seen of the worn surface of the neat MASF. Due to this reason, epoxy composite MASF-SCSP 20% can be seen of the debris was worn away from the interface, especially at the longer sliding distances. shows two regions of the neat composite surface as the end of the worn area (marked as W“”) and the generated epoxy debris from the interface (marked as „D“”). The better wear performance of epoxy composite- MASF-SCSP filler could be due to the enhancement of the adhesion characteristic between the oil palm fibres and the polyester matrix. It was reported that the interfacial adhesion of the oil palm fibres with the matrix enhanced the mechanical properties [5], where during the tensile loading condition, the break occurred in the composite and no sign of pull-out was observed. From tribological point of view, during the sliding, the possibility of pull-out or debonding could be lesser for the treated fiber than the untreated ones. In addition to that, there could be another reason, which is the porosity of the composite SEM micrographs of epoxy composite-MASF-SCSP 20% at 30 N applied load and 2.5 m/s sliding velocity. SEM micrographs of epoxy composite-MASF-SCSP 30% at 30 N applied load and 2.5 m/s sliding velocity. SEM micrographs of epoxy composite-MASF-SCSP 10% at 30 N applied load and 2.5 m/s sliding velocity. SEM micrographs of epoxy composite – MASF- SCSP30% shows no sign of debonding and/or empty bundles of fibres. This could contribute to the lower wear rate (higher wear resistance) values of epoxy composite-MASF-

SCSP30% compared to NSCSP, SCSP 10%, and SCSP 20% IV. CONCLUSION [The effects of applied load and sliding velocity were highly pronounced on the wear](#) rate. Higher wear rate was exhibited at higher load and sliding velocity. On the other hand, sliding velocity showed less effect on the frictional behaviour. Adding filler coconut shell charcoal powder (CSCP) to epoxy composite material reinforced Musa acuminata stem fiber (MASF) reduces wear rate or increases wear resistance about 40–60%. Wear resistance performance of epoxy composite material reinforced MASF was heavily influenced by interface fiber and its adhesion characteristics porosity, which allows it to be filled by the CSCP filler. The wear mechanism of the composite is dominated by debonding and fiber bending, whereas fragmentation and deformation in resinous proven area. In addition, the fiber without CSCP filler causes higher material displacement in comparison composite with CSCP filler. SOME OF THE ADVANAGES FROM THE ABOVE RESULTS The Material surfaces of epoxy composite reinforced MASF with CSCP filler showed less wear damage compared to without CSCP (NCSCP). There was no sign of fiber debonding and fiber empty (without filler), where the transfer of material appears to be on the resinous more fibrous areas of MASF without CSCP filler REFERENCES [1]. Nozawa JI, Komoto T, Kawai T, Kumehara H., 2009, "Tribological Properties of Polymer-Sheet-Adhered Metal Hybrid Gear". *Wear*, 266(9e10):893e. <https://doi.org/10.1016/j.wear.2008.12.008>. [2]. Srinath, G., Gnanamoorthy, R., 2005, "Effect of short fibre reinforcement on the friction and wear behaviour of nylon 66". *Appl. Compos. Mater.* 12(6), 369–383, doi:10.1007/s10443-005-5824-6. [3]. Senthilvelan, S., Gnanamoorthy, R.: Selective carbon fiber reinforced nylon 66 spur gears: development and performance. [4]. [5]. [6]. [7]. [8]. [9]. *Appl. Compos. Mater.* 13(1), 43–56 (2006). doi:10.1007/s10443-005-9003-6. Yousif, B.F., El-Tayeb, N.S.M., 2007, "Tribological evaluations of polyester composites considering three orientations of CSM glass fibres using BOR machine. *Appl. Compos. Mater.* 14(2), 105–116, doi:10.1007/s10443-007-9034-2. Yousif, B.F., El-Tayeb, N.S.M., 2006, "Mechanical and tribological properties of OPRP and CGRP composites". In: *International Conference of ICOMAST*, pp. 384–388. Malacca, Malaysia, 28–30 August. Navin, H., Dwivedi, U., 2006, "Effect of coupling agent on abrasive wear behaviour of chopped jute fibre-reinforced polypropylene Composites". *Wear* 261(10), 1057–1063 (2006). doi:10.1016/j.wear.01.039. [Holbery J, Houston D, 2006, "Natural-fiber-reinforced polymer composites in automotive applications. JOM \(J Occup Med\), 58\(11\):80e6. <https://doi.org/10.1007/s11837-006-0234-2>. Puglia D, Biagiotti J, Kenny JM., 2005, "A review on natural fibre based composites - Part II: application of natural reinforcements in composite materials for automotive industry". *J Nat Fibers*, 1\(3\):23e65. \[https://doi.org/10.1300/J395v01n03_03\]\(https://doi.org/10.1300/J395v01n03_03\). \[Omrani E, Menezes PL, Rohatgi PK., 2016, "State of the art on tribological behavior of polymer matrix composites reinforced with natural fibers in the green materials world", *Engineering Science Technology, International J*, 19\\(2\\):717e36. <https://doi.org/10.1016/j.jestch.10.007>. \\[10\\]. El-Tayeb, N.S.M., 2008, "Abrasive wear performance of untreated SCF reinforced polymer composite", *J. Mater. Process Technol.* 206\\(1–3\\), 305–314, doi:10.1016/j.jmatprotec.2007.12.028. \\[11\\]. El-Tayeb, N.S.M., Yousif, B.F., Yap, T.C., 2006, "Tribological studies of polyester reinforced with CSM 450-R-glass fiber sliding against smooth stainless steel counterface", *Wear* 261\\(3–4\\), 443–452, doi:10.1016/j.wear.2005.12.014. \\[12\\]. Gang D., 2018, "The influence of surface treatment on the tensile and tribological properties of wood fiber-reinforced polyimide composite". *Surf Interface Anal*, 50\\(3\\):304e10. <https://doi.org/10.1002/sia.6369>. \\[International Journal of Advances in Engineering and Management \\\(IJAEM\\\) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 International Journal of Advances in Engineering and Management \\\(IJAEM\\\) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 International Journal of Advances in Engineering and Management \\\(IJAEM\\\) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 International Journal of Advances in Engineering and Management \\\(IJAEM\\\) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 International Journal of Advances in Engineering and Management \\\(IJAEM\\\) Volume 3, Issue 5 May 2021, pp: 382-388\\]\\(#\\)\]\(#\)](#)

www.ijaem.net ISSN: 2395-5252 [International Journal of Advances in Engineering and Management \(IJAEM\)](#) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 [International Journal of Advances in Engineering and Management \(IJAEM\)](#) Volume 3, Issue 5 May 2021, pp: 382-388 www.ijaem.net ISSN: 2395-5252 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 382 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 383 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 384 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 385 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 386 DOI: 10.35629/5252-0305382388 [Impact Factor value 7.429](#) | [ISO 9001: 2008 Certified Journal Page](#) 387 DOI: 10.35629/5252-0305382388 Impact Factor value 7.429 | ISO 9001: 2008 Certified Journal Page 388